

GSM Scout active IP65

Monitoring and telecontrolling by SMS from your cell phone -
being informed directly, direct reaction, Plug and Play!

ConiuGo

ConiuGo GmbH
Gesellschaft für Telekommunikation

Order no.: 7001002135

Applications

Monitoring of:

- Sailors, boats & yachts
- Campers and caravans
- Home

Teleswitching of:

- Bilge pump
- Light
- Air conditioner



General information

The GSM Scout active IP65 is a cheap and easy solution for monitoring mobile objects like boats, yachts, caravans or campers. With connected sensors, the device detects e.g. Burglary, upcoming fire, water ingress or other negative incidents. Those are reported directly by SMS to an usable cell phone, which makes you able to react directly. The system is customized by the dial number storage of the SIM card and directly usable. It is also possible to activate the relay outputs by SMS. Therefore different devices on board can be switched on or off. For protecting the circuitries of burning damages, using a R/C protection combination is recommended.

Technical specific features

- Easy installation with screws
- No special software required
- Easy customization with SIM card
- Small dimensions, splashwaterproof (IP65)
- 2 relay contact for switching
- Transferring of prepaid credits
- Transferring of signal quality
- Variable alarm texts possible

Conditions

For using the GSM Scout active IP65 is required:
GSM antenna, main power supply 11-35 VDC,
SIM card (prepaid or contract), sensors

Technical data

Mobile phone network	Usable with all general mobile providers
Customization	SIM card customization by cell phone
Dimensions / weight	175 x 175 x 50 mm (W x L x H) / 300 g
Temperature range	- 30 °C until + 60 °C working temperature
Interfaces	1 register circle for "burglary" 1 register circle for "fire" 1 register circle "water" 1 register circle for "individual incident" 2 x relay contacts
Power supply	11 - 35 V DC , 65 mA

Scope of supply	GSM Scout active Ip65 Manual Miniature screwdriver for brackets Screws of the housing
------------------------	--

Optional accessoires	Power supply 230 V AC / 12 V DC Glas attached antenna (indoor), 1,5 m cable (SMA) Round antenna PUK (outdoor), 3 m cable (SMA) Lithium polymer battery R/C protection Different sensors on request	Order no.: 305307214 300303304S 300303310S 701100905/1 700100618
-----------------------------	---	--

06/2014